19" LED Widescreen Commercial Grade Monitor

Produces High Resolution Images with Vibrant Color





19LGLED2

FEATURES

- 1366 x 768 (720p) HD resolution
- VGA (D-Sub) input
- 5 ms response time means a quick refresh of the video image
- Super energy-saving mode reduces power consumption
- EPEAT Gold rating meets the highest criteria for environmental compliance
- VESA™ compliant wall mount



SPECIFICATIONS

Display	LCD Panel Type	19" Class (18.5" measured diagonally)	Resolution	PC Analog	1366 x 768
	Color	Black			
	Color Gamut	72%	Dimensions	Set w/Stand (W x D x H)	17.4" x 6.6" x 13.7"
	Color Depth	16.7 Million Colors		Set w/o Stand (W x D x H)	17.4" x 2.2" x 10.8"
	Pixel Pitch	0.3 mm		Box	20.0" x 13.3" x 4.5"
	Aspect Ratio	16:09	Weight		
	Maximum Resolution	1366 x 768	3	Set w/Stand	4.6 lbs
	Brightness	200 cd/m2		Set w/o Stand	4.2 lbs
	Contrast Ratio	700:1, DFC 5,000,000:1		Box	7.1 lbs
	Response Time	5ms			
	Viewing Angle (HxV)	90°/65°	Stand	Base	Detachable
	Surface Treatment	Non-Glare			Tilt (-5° Front ~ 20° Rear)
User Interface	PC Input	D-Sub	Certifications	Safety	TCO 5.2, UL (cUL), TUV-GS (TUV-
					Туре)
Power	Input	100~240V		EMC	FCC-B, CE
	Normal On (Typ.)	15W		EPEAT	Gold
	Stand-by Usage	0.3W		EPA	Yes
				VESA Mounting	75mm x 75mm
Frequency	Analog/Digital	30~83kHz (H-Frequency) 56~75Hz (V-Frequency)		Microsoft Logo	Window 7
			Special Features		de (ARC), Intelligent Auto (Auto
Language	Set-up	English, Germanic, French, Spanish, Italian, Swedish, Finnish, Portuguese, Polish, Russian, Greek, Chinese,		Resolution), Plug & Play - DDC2B, DDC/CI, HDCP, Super Energy	
				Saving	
				D 0 1 D C 1 O 1	
		Japanese, Korean, Ukrainian, Portuguese (Brazil), Hindi	Accessories	Power Cord, D-Sub Cable	
		r orruguese (brazil), r in di			