



ALIBI™

High Definition Surveillance



3.0 Megapixel

HD-TVI

3.0 MEGAPIXEL HD-TVI 65' IR OUTDOOR BULLET SECURITY CAMERA

Send HD video over standard RG59 coax cable

- + 3.0 MP High-Performance CMOS, with active imaging pixel array of 2052 x 1536, produces up to 3.0 MP HD-quality video
- + 2.8 mm wide angle lens provides an 84.0° FOV (Field of Vision) and covers a large area
- + Innovative Full Frame Illumination technology reduces overexposure of the IR LEDs at the center of the image, increases illuminant efficiency up to 30%, produces LED light in rectangle form to better fit screen size, and captures images up to 65' in the dark without washing out the subject at closer ranges
- + An ideal 24/7 surveillance solution with features such as True Day/Night (ICR) and 120dB Wide Dynamic Range (WDR)
- + HD-TVI delivers zero latency HD video over RG59 coax or any standard analog CCTV cabling, minimizing upgrade efforts
- + Up the Coax (UTC) technology enables you to control the camera's onscreen display (OSD) from your web browser, digital video recorder interface such as the Alibi Central Management System or smart phone app
- + Temperature rating of -40° to 140°F allows camera to operate in extreme weather conditions
- + IP66 weather-rated enclosure ensures the camera is protected from particles such as dust and sand

What's Included:

- + 3.0 MP HD-TVI IR Outdoor Bullet Security Camera
- + Mounting template
- + Mounting hardware
- + Quick start guide



3.0 MEGAPIXEL HD-TVI 65' IR OUTDOOR BULLET SECURITY CAMERA

SPECIFICATIONS

IMAGING SPECIFICATIONS

AGC Control	Built-in
Digital Noise Reduction (DNR)	Yes
S/N (dB)	62 dB
Effective Pixels (K)	2052 (H) x 1536 (V)
IR Array Range (ft)	65'
Max Analog IPS (NTSC)	18 fps
Megapixel	3.0
OSD	Yes - UTC
Wide Dynamic	Yes - WDR 120 dB

LENS SPECIFICATIONS

Focal Length (mm)	2.8 mm
FOV (degrees)	84°

CONNECTORS

Video Out	HD-TVI BNC
-----------	------------

POWER REQUIREMENTS

Power Consumption (watts/mA)	5 Watts
Power Supply Included	No
Volts DC Input	12 Vdc

PHYSICAL CHARACTERISTICS

Dimensions (in)	2.30" x 2.19" x 6.05"
Relative Humidity	Humidity 90% or less (non-condensing)
Operating Temperature (F)	-40°F - 140°F
Product Color	White
Ingress Protection Rating	IP66
Weight (lb)	.82
Shipping Weight	1