



3.0 Megapixel



3.0 MEGAPIXEL HD-TVI 130' IR OUTDOOR VARIFOCAL SECURITY CAMERA

Motorized zoom conveniently addresses varying viewing needs

- + 3.0 MP High-Performance CMOS, with active imaging pixel array of 2052 x 1536, produces up to 3.0 MP HD-quality video
- + 2.8-12 mm motorized zoom lens offers flexibility
- + Cutting-edge Full Frame Illumination technology with long-range IR reduces overexposure of the IR LEDs at the center of the image, increases illuminant efficiency up to 30%, produces LED light in rectangle form to better fit screen size, and captures images up to 130' in the dark without washing out the subject at closer ranges.
- + 120dB Wide Dynamic Range (WDR) and True Day/Night (ICR) features produce more detailed images any time of day, making this an ideal 24/7 solution
- + HD-TVI delivers zero latency HD video over RG59 coax or any standard analog CCTV cabling, minimizing upgrade efforts
- + Up the Coax (UTC) technology enables you to control the camera's onscreen display (OSD) from your web browser, digital video recorder interface such as the Alibi Central Management System or smart phone app.
- + Temperature rating of -40° to 140°F ensures camera operates in extreme weather conditions
- + IP66 weather-rated enclosure ensures the camera is protected from particles such as dust and sand

What's Included:

- + 3.0 MP HD-TVI IR Outdoor Varifocal Security Camera
- + Mounting template
- + Mounting hardware
- + Quick start guide

SPECIFICATIONS

Shipping Weight

IMAGING SPECIFICATIONS	
AGC Control	Built-in
Digital Noise Reduction (DNR)	Yes
S/N (dB)	62 dB
Effective Pixels (K)	2052 (H) x 1536 (V)
IR Array Range (ft)	130'
Max Analog IPS (NTSC)	18 fps
Megapixel	3.0
OSD	Yes - UTC
Wide Dynamic	Yes - WDR 120dB
LENS SPECIFICATIONS	
Focal Length (mm)	2.8-12 mm Motorized Zoom
CONNECTORS	
Video Out	HD-TVI BNC
Video Out POWER REQUIREMENTS	HD-TVI BNC
	9 Watts
POWER REQUIREMENTS	
POWER REQUIREMENTS Power Consumption (watts/mA)	9 Watts
POWER REQUIREMENTS Power Consumption (watts/mA) Power Supply Included	9 Watts No
POWER REQUIREMENTS Power Consumption (watts/mA) Power Supply Included Volts AC Input	9 Watts No 24 Vac
POWER REQUIREMENTS Power Consumption (watts/mA) Power Supply Included Volts AC Input Volts DC Input	9 Watts No 24 Vac
POWER REQUIREMENTS Power Consumption (watts/mA) Power Supply Included Volts AC Input Volts DC Input PHYSICAL CHARACTERISTICS	9 Watts No 24 Vac 12 Vdc
POWER REQUIREMENTS Power Consumption (watts/mA) Power Supply Included Volts AC Input Volts DC Input PHYSICAL CHARACTERISTICS Dimensions (in)	9 Watts No 24 Vac 12 Vdc 3.62" × 3.34" × 3.34"
POWER REQUIREMENTS Power Consumption (watts/mA) Power Supply Included Volts AC Input Volts DC Input PHYSICAL CHARACTERISTICS Dimensions (in) Relative Humidity	9 Watts No 24 Vac 12 Vdc 3.62" × 3.34" × 3.34" Humidity 90% or less (non-condensing)
POWER REQUIREMENTS Power Consumption (watts/mA) Power Supply Included Volts AC Input Volts DC Input PHYSICAL CHARACTERISTICS Dimensions (in) Relative Humidity Operating Temperature (F)	9 Watts No 24 Vac 12 Vdc 3.62" × 3.34" × 3.34" Humidity 90% or less (non-condensing) -40 °F - 140 °F
POWER REQUIREMENTS Power Consumption (watts/mA) Power Supply Included Volts AC Input Volts DC Input PHYSICAL CHARACTERISTICS Dimensions (in) Relative Humidity Operating Temperature (F) Product Color	9 Watts No 24 Vac 12 Vdc 3.62" × 3.34" × 3.34" Humidity 90% or less (non-condensing) -40 °F - 140 °F White

2